



# GLASSWASHER AX-40

Rack size 400 mm x 400 mm and door clearance 300 mm.



WARE WASHING  
COMMERCIAL GLASSWASHERS



## “Easy grip” door: new design with integrated door handle

- ✓ The integration of the components provides greater resistance and robustness.
- ✓ Designed to have no corners or areas that are difficult to access: prevents deposits of dirt and facilitates cleaning.
- ✓ Its ergonomic handle provides a perfect grip, even with wet hands.
- ✓ Double-walled door with safety microswitch and high quality seal
- ✓ 30 cm load capacity: high versatility for washing a wide range of glasses and even medium-sized dishes.

## Warewashing, made simple

- ✓ Active Xperience: simple and intuitive use
- ✓ Dedicated cycles: selection of the ideal washing programme using icons.
- ✓ Electronic control panel with IP65 humidity protection.

## You will never WASH ALONE

- ✓ Tech-Services: our team of technicians will help you so that your machine is always ready for use.
- ✓ Design Services: tell us what your needs are and we will advise you.
- ✓ 60 years of experience and know-how at your disposal.

## INCLUDES

- ✓ Peristaltic Detergent Pump.
- ✓ Rinse aid pump.
- ✓ 1 glasses basket.
- ✓ 1 mixed basket (plates).
- ✓ 1 small basket for cutlery.

## OPTIONAL

- Overflow drainage pump. Tank water renewal by the principle of density.
- Double-level accessory for washing two baskets at the same time.

## ACCESSORIES

- Manual water softeners
- Automatic water softeners
- 400X400 mm. baskets
- Inserts & supplements
- High Feet Kit
- Reverse Osmosis device OS-140P

## SPECIFICATIONS

Basket dimensions: 400 mm x 400 mm

Maximum glass height: 300 mm

Cycle duration: 90 / 120 / 180 “

Production baskets/hour: 40 / 30 / 20

Boiler capacity: 3.2 l

Wash tank capacity: 9 l

Water consumption/cycle: 2.2 l

### Loading

- ✓ Pump: 250 W / 0.33 Hp
- ✓ Tank: 1200 W
- ✓ Boiler: 2500 W
- ✓ Total loading: 2750 W

Electrical supply: 230 V / 50 Hz / 1 ~ (12 A)

Electrical connection: --

### External dimensions (WxDxH)

- ✓ Width: 470 mm
  - ✓ Depth: 537 mm
  - ✓ Height: 710 mm
- Net weight: 36.5 Kg

## SALES DESCRIPTION

Sani-Control: guaranteed disinfection  
 Embedded bodywork and easy-grip door: hygienic and ergonomic  
 Exclusive Hydroblade™ washing arms: maximum effectiveness.  
 3-stage filtering system.  
 Double-walled body (partial).

### Sani-Control guarantee

- ✓ GUARANTEED DISINFECTION in compliance with standard DIN 10534.
- ✓ THERMAL LOCK function: Ensures that rinsing will be carried out at the ideal temperature to disinfect the dishes.

### New recessed bodywork

- ✓ Ergonomic design with rounded corners to prevent the accumulation of dirt and facilitate cleaning.
- ✓ Compact tank volume (50% water saving compared to the previous range).
- ✓ Embedded basket guides

### Hydroblade™ washing arms

- ✓ Redesigned nozzles for greater washing performance.
- ✓ The “monoblock” design delivers durability and resistance to impacts.
- ✓ 30% savings in water consumption during rinsing compared to the previous range.

### 3-stage filter system: surface, tank and extraction

- ✓ Keeps the washing water in optimal conditions to maintain constant washing performance.
- ✓ The surface filters feature an “easy-on” design and can be quickly removed without having to disconnect the washing arms.





# GLASSWASHER AX-40

Rack size 400 mm x 400 mm and door clearance 300 mm.



WARE WASHING  
COMMERCIAL GLASSWASHERS

Noise level (1m.): <69 dB(A)

### Crated dimensions

525 x 615 x 820 mm

### AVAILABLE MODELS

1303083	Glasswasher AX-40 230/50/1
1303090	Glasswasher AX-40B 230/50/1
1303091	Glasswasher AX-40B 220/60/1

\* Ask for special versions availability



[www.sammic.co.uk](http://www.sammic.co.uk)

Food Service Equipment Manufacturer

Unit 2, Trevanah Road  
Troon Industrial Park  
LE4 9LS - Leicester

[uksales@sammic.com](mailto:uksales@sammic.com)  
Tel.: +44 0116 246 1900



Project	Date
Item	Qty
Approved	

product sheet  
updated 27/07/2022